

TPG 361 controller for 1 gauge





TPG 361 controller for 1 gauge

- Universal power supply units for worldwide use
- For connecting various types of gauges
- Simple to operate and good reading precision
- For operation of one gauge with analog output signal
- Brilliant display
- Two configurable relay set points
- Versatile connectivity: USB, RS-485, Ethernet
- Direct data storage on USB flash memory (data and settings)
- Can be used as table top or as rack mount unit

TPG 361 controller for 1 gauge
1
10 1/s
60 V DC, 0,5 A; 30 V AC, 1 A
1 piece
0.75/0.15/0.02 s
USB, RS-485, Ethernet
50/60 Hz
<= 45 VA
100-240 V
55,000 hPa 41,250 Torr 55,000 mbar
5 · 10 ⁻¹¹ hPa 3.75 · 10 ⁻¹¹ Torr 5 · 10 ⁻¹¹ mbar
100 1/s
1
IP 20
CE, UL
2 pieces
0,5; 1 A
60 V DC; 30 V DC
0-10 V
5-50 °C 41-122 °F 278-323 K
-20-60 °C -4-140 °F 253-333 K
1.1 kg 2.43 lb

Order number	
TPG 361	PT G28 040

Accessories	
Accessory for ActiveLine gauges and controllers	
Mating connector	B 4707 283 MA
Sensor cable, 10 m	PT 448 252 -T
Sensor cable, 15 m	PT 448 253 -T
Sensor cable, 1 m	PT 448 248 -T
Sensor cable, 20 m	PT 448 254 -T
Sensor cable, 25 m	PT 448 255 -T
Sensor cable, 30 m	PT 448 256 -T
Sensor cable, 35 m	PT 448 257 -T
Sensor cable, 3 m	PT 448 250 -T
Sensor cable, 40 m	PT 448 258 -T
Sensor cable, 45 m	PT 448 259 -T
Sensor cable, 50 m	PT 448 260 -T
Sensor cable, 6 m	PT 448 251 -T
Software for display and data logging for ActiveLine	PT 882 550 -T



Vacuum solutions from a single source

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

Complete range of products

From a single component to complex systems: We are the only supplier of vacuum technology that provides a complete product portfolio.

Competence in theory and practice

Benefit from our know-how and our portfolio of training opportunities! We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a perfect vacuum solution? Please contact us:

Pfeiffer Vacuum GmbH
Headquarters · Germany
T +49 6441 802-0
info@pfeiffer-vacuum.de
www.pfeiffer-vacuum.com