



# CenterThree controller for 3 gauges



Similar Image

## CenterThree controller for 3 gauges

- For the operation of three Centerline gauges
- Brilliant display
- Simultaneous display of both
- Four freely configurable relay switching points
- Versatile connectivity: writer, USB, Ethernet
- Direct data storage on USB flash memory (data and settings)
- Can be used as table top or as rack mount unit

Technical Data	CenterThree controller for 3 gauges
Connection for gauge	3
Display rate	≥ 10 Hz
Error signal: Switching voltage max.	60 V DC, 0,5 A; 30 V AC, 1 A
Error signal: Working contact, potential-free	1 Stück
Filter time constant	8/0, 8/0, 16 s
Interface	Schreiber, USB, Ethernet
Mains requirement: frequency (range)	50/60 Hz
Mains requirement: power consumption	≥ 65 VA
Mains requirement: voltage (range)	100-240 V
Measurement range	Depending on gauge
Measurement rate	≥ 100 Hz
Measuring channel	3
Protection category	IP30
Safety	CE, UL
Set point: Changeover contact, potential-free	6 assignable
Set point: Current max.	0.5;1 A
Set point: Voltage max.	60 V DC, 30 V AC
Signal output: Measuring value, analog	-5-+14.5 V
Temperature: Operating	5-50 °C
Temperature: Storage	20 – 60 °C
Weight	1.1 kg   2.43 lb

Order number	
CenterThree	<b>PT G28 330</b>

<b>Accessories</b>	
<b>Measurement cable D-Sub</b>	
Gauge cable D-Sub, 15 pol, for CenterOne, CenterTwo, CenterThree, 10 m	<b>PT 448 552 -T</b>
Gauge cable D-Sub, 15 pol, for CenterOne, CenterTwo, CenterThree, 15 m	<b>PT 448 553 -T</b>
Gauge cable D-Sub, 15 pol, for CenterOne, CenterTwo, CenterThree, 20 m	<b>PT 448 554 -T</b>
Gauge cable D-Sub, 15 pol, for CenterOne, CenterTwo, CenterThree, 30 m	<b>PT 448 556 -T</b>
Gauge cable D-Sub, 15 pol, for CenterOne, CenterTwo, CenterThree, 50 m	<b>PT 448 560 -T</b>
Gauge cable D-Sub, 15 pol, for CenterOne, CenterTwo, CenterThree, 5 m	<b>PT 448 551 -T</b>
Measurement cable D-Sub, 15 pol, for CenterOne, CenterTwo, CenterThree, 3 m	<b>PT 448 550 -T</b>
<b>Measurement cable FCC</b>	
Gauge cable FCC/RJ45, for CenterOne, CenterTwo, CenterThree, 10 m	<b>PT 448 452 -T</b>
Gauge cable FCC/RJ45, for CenterOne, CenterTwo, CenterThree, 15 m	<b>PT 448 453 -T</b>
Gauge cable FCC/RJ45, for CenterOne, CenterTwo, CenterThree, 20 m	<b>PT 448 454 -T</b>
Gauge cable FCC/RJ45, for CenterOne, CenterTwo, CenterThree, 30 m	<b>PT 448 456 -T</b>
Gauge cable FCC/RJ45, for CenterOne, CenterTwo, CenterThree, 3 m	<b>PT 448 450 -T</b>
Gauge cable FCC/RJ45, for CenterOne, CenterTwo, CenterThree, 50 m	<b>PT 448 460 -T</b>
Gauge cable FCC/RJ45, for CenterOne, CenterTwo, CenterThree, 5 m	<b>PT 448 451 -T</b>

## **VACUUM SOLUTIONS FROM A SINGLE SOURCE**

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

## **COMPLETE RANGE OF PRODUCTS**

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

## **COMPETENCE IN THEORY AND PRACTICE**

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a  
perfect vacuum solution?  
Please contact us:

**Pfeiffer Vacuum GmbH**  
Headquarters · Germany  
T +49 6441 802-0  
info@pfeiffer-vacuum.de

[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

All data subject to change without prior notice.

**PFEIFFER**  **VACUUM**