



TTR 91, Pirani gauge, DN 16 ISO-KF







Similar Image

- Connector FCC 68/RJ45, 8-pole
- For general vacuum applications
- Compact and rugged
- Maximum pressure refers to inert gases

Technical Data	TTR 91, Pirani gauge, DN 16 ISO-KF
Accuracy: 10 ⁻³ - 10 ² hPa	±15 %
Bakeout temperature	80 °C
Feedthrough	Glass
Filament	Tungsten
Flange	Edelstahl
Measurement range max.	1 · 10 ³ hPa 0.75 · 10 ³ Torr 1 · 10 ³ mbar
Measurement range min.	5 · 10 ⁻⁴ mbar
Method of measurement	Pirani
Nominal diameter	DN 16 ISO-KF
Output signal: Measurement range	1.9-10 V
Output signal: Minimum load	10 kΩ
Output signal: Sensor error below	0.5 V
Protection category	IP40
Repeatability: 10 ⁻³ - 10 ² hPa	±2 %
Resolution	1 % of measurement
Response time	80 ms
Seal	Metal
Sensor cable length max.	<100 m (8·0.14 mm²)
Supply: Power consumption max.	≤ 1 W
Supply: Voltage	14-30 V DC
Temperature: Operating	5-60 °C
Temperature: Storage	20 – 65 °C
Volume	1.5 cm ³
Weight	80 g

Order number	
TTR 91	PT T10 138 300
Accessories	

Accessories	
Measurement cable FCC	
Gauge cable FCC/RJ45, for CenterOne, CenterTwo, CenterThree, 3 m	PT 448 450 -T
Vacuum accessories	
Centering ring with metal mesh-fine filter, pore size 4 m, FPM/stainless steel	PT 120 132 -T
Centering ring with protection filter,	PF 117 216 -T

VACUUM SOLUTIONS FROM A SINGLE SOURCE

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

COMPLETE RANGE OF PRODUCTS

From a single component to complex systems: We are the only supplier of vacuum technology that provides a complete product portfolio.

COMPETENCE IN THEORY AND PRACTICE

Benefit from our know-how and our portfolio of training opportunities! We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a perfect vacuum solution? Please contact us:

Pfeiffer Vacuum GmbH Headquarters · Germany T +49 6441 802-0 info@pfeiffer-vacuum.de

www.pfeiffer-vacuum.com